

BLACK STRIPPING PAD

PRODUCT SPECIFICATIONS

The Black Stripping Pad is constructed of polyester fibers in an open texture nonwoven fabrication. Abrasive particles are distributed throughout the pad and adhered to the nonwoven construction with a sturdy adhesive.

Use

Use with Columbus Radical to remove worn and soiled floor finishes or sealers. May also be used to clean heavily soiled hard surface floors, such as concrete, PVC, linoleum, epoxy, vinyl, slightly porous and artificial stone floors. For use on standard electric floor machines (R44 standard-speed Rotary) or automatic scrubbers (GT50). Ideal for use on machines speeds up to 350rpm.

Directions for Use

Dust mop or sweep floor prior to stripping. Use pad attached to an R44 standard-speed Rotary machine until soil and finish are removed from floor. Pick up stripping or cleaning solution with a mop, wet vacuum (Cyclone 20 or 50) or automatic scrubber (GT50). Rinse floor and let dry prior to recoating or opening to traffic.

Construction

The Black Stripping Pad is constructed of polyester fibers along with synthetic adhesives that will not be notably affected by water or cleaners used in standard floor maintenance. The abrasives used in this product are synthetic. **This pad has been designed for use on both sides.**

Environmental Initiatives

Polyester fiber used in our pads come from 100% post-consumer and industrial recycled waste product.

Full Cycle™, formulated to biodegrade in a fraction of the time that it takes conventional floor pads once discarded into an active landfill.

Water Based Latex Resins are used in the manufacturing process. No phenol-formaldehyde resins are used in our binding process.

Shipping cartons contain at least 45% recycled material.

Plant is operating under EPA approved Clean Air Permit.

In-house water treatment has reduced our waste water flow by 83%.

Product Care

To prolong the life of this product it may be washed using a hose with a pressure spray nozzle to remove soil. To dissolve heavy soil or finish this pad may be soaked in detergent or diluted stripping solution prior to washing.

Sizes and Codes

Pack size: 5 units per pack.

400mm	(PAFL-1400)
425mm	(PAFL-1401)
450mm	(PAFL-1402)
500mm	(PAFL-1403)
550mm	(PAFL-1404)

Properties

Property	Value
Thickness (nominal)	24 mm
Weight	1628 gsm
Fiber Type	Recycled Polyester
Binder System	Cross-linkable water based
Binder Application	Spray/Dip
Abrasive Application	Spray/Dip
Abrasive	Yes
Color	Black
Pack	5 per bag

Note: Due to the intrinsic properties of the material and variable conditions of use, there may be slight variations in the specifications and results.

**Also available in
Red, Blue and White.**