

LUSTER LITE

ultra high speed burnishing pad

PRODUCT SPECIFICATIONS

The Luster Lite floor maintenance UHS burnishing pad is constructed of polyester fibers in a textured nonwoven fabrication.

Use

This pad is used to burnish/polish floor finish to a high gloss. Recommended for use on all finishes. Excellently suited for top dressing highly polished floors. Ideal for use on machines speeds up to 3000 rpm.

Directions for Use

Dust mop floors prior to burnishing. Use pad until finish gives high gloss. Dust mop again to remove dust from burnishing.

Construction

The Luster Lite Ultra High Speed Burnishing Pad is made of 100% recycled polyester fibers and water based resins. **This pad has been designed for use on both sides.**

Environmental Initiatives

Polyester fiber used in our pads come from 100% post-consumer and industrial recycled waste product.

Full Cycle™, formulated to biodegrade in a fraction of the time that it takes conventional floor pads once discarded into an active landfill.

Water Based Latex Resins are used in the manufacturing process. No phenol-formaldehyde resins are used in our binding process.

Shipping cartons contain at least 45% recycled material.

Plant is operating under EPA approved Clean Air Permit.

In-house water treatment has reduced our waste water flow by 83%.

Product Care

To prolong the life of this product it may be washed using a hose with a pressure spray nozzle to remove soil. Allow pad to dry completely before using again.

Sizes and Codes

500mm(PAFL-1420)

Properties

| Property | Value |
|----------------------|----------------------------|
| Thickness | 26 mm |
| Weight | 983 gsm |
| Fiber Type | Recycled Polyester |
| Binder System | Cross-linkable water based |
| Binder Application | Spray/Dip |
| Abrasive Application | N/A |
| Abrasive | N/A |
| Color | Light Blue |
| Pack | 5 per bag |

Note: Due to the intrinsic properties of the material and variable conditions of use, there may be slight variations in the specifications and results.

